Amendments to the Claims

This listing of claims replaces all prior listings (versions) of claims.

1. (Currently amended) A character recognition system, comprising:

an optical character reader system for collecting character data by electro-optically scanning printed characters;

a conversion system for converting the character data to a Magnetic Ink Character Recognition (MICR) format from a non-MICR format; and

a recognition engine for interpreting the converted character data using a MICR algorithm.

wherein the conversion system scales the character data to a pel density associated with <u>data obtained by a character recognition device using</u> a multigap MICR read head.

- (Original) The character recognition system of claim 1, wherein the optical character reader system scans at a pel density in a range of approximately 200 to 600 dpi.
- (Original) The character recognition system of claim 1, wherein the character data is stored in a grey scale image format.
- 4. (Cancelled).
- 5. (Previously presented) The character recognition system of claim 1, wherein the conversion system scales the character data to approximately 0.33 millimeters/pixel in a horizontal dimension and 0.43 millimeters/pixel in a vertical dimension.

10/081.417 3

- (Original) The character recognition system of claim 3, wherein the conversion system converts the grey scale image format to a black and white image format.
- (Original) The character recognition system of claim 1, wherein the printed characters are printed in an E13B font.
- (Currently amended) A method for performing character recognition, comprising: collecting character data by electro-optically scanning printed characters; converting the character data to a Magnetic Ink Character Recognition (MICR) format from a non-MICR format; and

interpreting the converted character data using a MICR algorithm;

wherein the converting step scales the character data to a pel density associated with
data obtained by a character recognition device using a multigap MICR read head.

- (Original) The method of claim 8, wherein the character data is scanned at a pel density in a range of approximately 200 to 600 dpi.
- 10. (Original) The method of claim 8, wherein the collection step stores the character data in a grey scale image format.
- 11. (Cancelled).
- 12. (Original) The method of claim 8, wherein the converting step seales the character data to approximately 0.33 millimeters/pixel in a horizontal dimension and 0.43 millimeters/pixel in a vertical dimension

10/081.417 4

- 13. (Original) The method of claim 10, wherein the converting step converts the grey scale image format to a black and white image format.
- 14. (Original) The method of claim 8, wherein the printed characters are printed in an E13B font
- 15. (Currently amended) A program product stored on a computer readable medium for performing character recognition, comprising:

means for accessing character data collected by an electro-optical scanning system;
means for converting the character data to a spatial resolution and density as if
captured by a Magnetic Ink Character Recognition (MICR) read head; and
means for interpreting the converted character data using a MICR algorithm;
wherein the converting means scales the character data to a pel density associated
with data obtained by a character recognition device using a multigap MICR read head.

- 16. (Original) The program product of claim 15, wherein the character data comprises a pel density in a range of approximately 200 to 600 dpi.
- 17. (Cancelled).
- 18. (Original) The program product of claim 15, wherein the converting means scales the character data to approximately 0.33 millimeters/pixel in a horizontal dimension and 0.43 millimeters/pixel in a vertical dimension.
- 19. (Original) The program product of claim 15, wherein the converting means converts a grey scale image format to a black and white image format.

10/081,417 5

- (Original) The program product of claim 15, wherein the character data collected by the electro-optical scanning system comprises characters printed in an E13B font.
- 21. (Currently amended) A multi-voting character recognition engine for analyzing an inputted set of printed characters, comprising:
- a plurality of character recognition systems, wherein each character recognition system independently analyzes the inputted set of printed characters, and wherein one of the character recognition systems includes:

an optical character reader system for collecting character data by electro-optically scanning printed characters;

a conversion system for converting the character data to a Magnetic Ink Character Recognition (MICR) format; and

a recognition engine for interpreting the converted character data using a MICR algorithm; and

a voting system for combining results from each of the plurality of character recognition systems and determining a recognized set of characters;

wherein the conversion system scales the character data to a pel density associated with data obtained by a character recognition device using a multigap MICR read head.

22. (Original) The multi-voting character recognition engine of claim 21, wherein the inputted set of printed characters are printed in an E13B font.

10/081.417 6